● PRINTER RUSH ● (PTO ASSISTANCE)

Application :	10 611 457	Examiner :	B Lee	GAU:	2632
From:	mg	Location:	FMF FDC	Date:	0/. 63.66
		Tracking #:	10 611457 EPM	Week Date:	09.19.05
[RUSH] MESSA	OC CODE 1449 IDS CLM IIFW SRFW DRW OATH 312 SPEC	O9-24-05	MISCELI Continuing Foreign Pri Document Fees Other	Data ority	
on pag	ge i, line s Mease provid				panks.
[XRUSH] RESP	PONSE:			INITI	AKS: Py

NOTE: This form will be included as part of the official USPTO record, with the Response document coded as XRUSH.

REV 10/04

Express Mill" Label No.: EV 134752951 U.S	OIPE
Date of Deposit: 9-1-03 hereby certify that this paper or fee is being deposited with he United States Postal Service "Express Mail Post Office to	SEP 2 4 2004
Iddressee" service under 37 CFR 1.10 on the date indicated bove and is addressed to Mail Stop Patent Application,	TRADERI RITA

Docket No. 14247US01

Brenda K. Johnson

Typed or printed name of person mailing paper or fee)

Signature of person mailing paper or fee)

Commissioner for Patents, P.O. Box 1450, Alexandria, VA

2313-1450.

ACOUSTIC WAVE ICE AND WATER DETECTOR

CROSS-REFERENCE TO RELATED APPLICATIONS

This application is related to U.S. patent application entitled "Torsional Acoustic Wave Sensor," Serial No. 106/1583, filed concurrently herewith and U.S. patent application entitled "Acoustic Wave Touch Detection Circuit and Method," Serial No. 10/454,003, filed June 4, 2003.

STATEMENT REGARDING FEDERALLY SPONSORED RESEARCH OR DEVELOPMENT

N/A

FIELD OF INVENTION

15

20

10

The present invention relates to an acoustic wave sensor utilizing one or more acoustic waves trapped in an acoustic wave cavity for detecting the presence of one substance or more than one substance on the surface of the cavity. In one embodiment, the acoustic wave sensor forms an ice detector and in another embodiment, the sensor forms and ice and water detector although the acoustic wave sensor of the present invention can be used to sense the presence of other substances as well.

BACKGROUND OF THE INVENTION

25

Ice detectors are known that utilize acoustic waves propagating over a distance through a structure, such as the outer material of an airplane wing, wherein the acoustic waves propagate between a transmitter transducer and a receiver transducer. Propagating waves are